



Product Name: Liquid Breaker Page: 1 of 8

This revision issued: April 2024

Section 1 - Identification of The Material and Supplier

aiMix Chemicals Pty Ltd

52-54 Power St

St Marys, NSW 2760

Phone: 0432388640 (24 hours)

Email: qc@aimixchemicals.com.au

Chemical nature: Water solution of sodium hydroxide.

Trade Name: Liquid Breaker

Product Use: Chemical intermediate; many industrial uses.

Creation Date: July, 2005

This version issued: April 2024 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 1126 from anywhere in Australia

Section 2 - Hazards Identification

This product is classified as: Hazardous according to the criteria of SWA Australia GHS7.

GHS7 SIGNAL WORD:

Danger.



HAZARD STATEMENT:

H302: Harmful if swallowed.

H314: Causes severe skin burns and eye damage.

H335: May cause respiratory irritation.

H402: Harmful to aquatic life due to extreme pH.

PREVENTION

P102: Keep out of reach of children.

P260: Do not breathe fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well ventilated area.

P273: Avoid release to the environment.

P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

P337: If eye irritation persists: seek medical attention.

P363: Wash contaminated clothing before reuse.

P301+P312: IF SWALLOWED: Call a POISON CENTER or doctor if you feel unwell.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P370+P378: Not combustible. Use extinguishing media suited to burning materials.

STORAGE

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL

P501: If no in-house recycle or reclaim resources are suitable for this product, contact a specialist waste disposal company (see Section 13 of this SDS).

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd Phone: 0432388640 (24 hours)





Product Name: Liquid Breaker Page: 2 of 8

This revision issued: April 2024

Major Health Hazards: causes severe burns, may cause serious damage to eyes, harmful if swallowed, respiratory tract irritant.

DANGEROUS GOODS CLASS: 8

Section 3 - Composition/Information on In	ngredients
---	------------

Ingredients	CAS No	Conc,%
Sodium hydroxide Pearl	1310-73-2	50
Other non hazardous ingredients	various	to 100

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

Inhalation: If inhalation occurs, contact a Poisons Information Centre, or call a doctor at once. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. DO NOT allow victim to move about unnecessarily. Symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Seek urgent medical attention. Flush contaminated area with lukewarm, gently flowing water for at least 60 minutes, by the clock. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this SDS and take their advice). Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands, belts). Strongly basic ingredients tend to penetrate the skin and so need longer rinsing than other substances.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for at least 60 minutes, by the clock, while holding the eyelid(s) open. Neutral saline solution may be used as soon as it is available. DO NOT INTERRUPT FLUSHING. If necessary, keep emergency vehicle waiting (show paramedics this SDS and take their advice). Take care not to rinse contaminated water into the unaffected eye or onto face. Call a Poisons Information Centre or a doctor urgently.

Ingestion: If swallowed, rinse mouth thoroughly with water and contact a Poisons Information Centre. Urgent hospital treatment is likely to be needed. Give activated charcoal if instructed.

PPE for First Aiders:

Wear rubber boots, overalls, gloves, apron, face shield. Available information suggests that gloves made from nitrile rubber should be suitable for intermittent contact. However, due to variations in glove construction and local conditions, the user should make a final assessment. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storing or re-using.

Notes to physician: Treat symptomatically. Can cause corneal burns

Section 5 - Fire Fighting Measures

Hazchem Code: 2R

Fire and Explosion Hazards: There is no risk of an explosion from this product under normal circumstances if it is involved in a fire. This product is likely to decompose only after heating to dryness, followed by further strong heating. Fire decomposition products from this product are not expected to be hazardous or harmful.

Extinguishing Media: Water fog or fine spray is the preferred medium for large fires. Aim to dilute the material with large quantities of water. If practical, contain diluted material and prevent from entering drains and water courses.

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd Phone: 0432388640 (24 hours)





Product Name: Liquid Breaker Page: 3 of 8

This revision issued: April 2024

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade. There is little danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is liquid-tight chemical protective clothing and breathing apparatus.

Specific hazards: Non-combustible material.

Fire fighting further advice: Not combustible, however following evaporation of aqueous component residual material can burn if ignited.

Section 6 - Accidental Release Measures

Accidental release:

LARGE SPILL:

In the event of a major spill, prevent spillage from entering drains or water courses. Evacuate the spill area and deny entry to unnecessary and unprotected personnel. Wear full protective chemically resistant clothing including eye/face protection, gauntlets and self contained breathing apparatus. See below under Personal Protection regarding Australian Standards relating to personal protective equipment. Suitable materials for protective clothing include rubber, Viton, Nitrile, butyl rubber, Barricade, neoprene, Teflon, polyethylene, PE/EVAL, Saranex, Responder. Eye/face protective equipment should include a full face shield. If there is a significant chance that vapours or mists are likely to build up in the cleanup area, we recommend that you use a respirator. Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned below (section 8).

SMALL SPILLS

Stop leak if safe to do so, and contain spill. Absorb onto sand, vermiculite or other suitable absorbent material. If spill is too large or if absorbent material is not available, try to create a dike to stop material spreading or going into drains or waterways. Because of the corrosiveness of this product, special personal care should be taken in any cleanup operation. Sweep up and shovel or collect recoverable product into labelled containers for recycling or salvage, and dispose of promptly. Recycle containers wherever possible after careful cleaning. After spills, wash area preventing runoff from entering drains. If a significant quantity of material enters drains, advise emergency services. Contaminated area may be neutralised by washing with weak or dilute acid. Vinegar, citrus juice and most soft drinks may be suitable. This material may be suitable for approved landfill. Ensure legality of disposal by consulting regulations prior to disposal. Thoroughly launder protective clothing before storage or re-use. Advise laundry of nature of contamination when sending contaminated clothing to laundry.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: This product is a Scheduled Poison. Observe all relevant regulations regarding sale, transport and storage of this schedule of poison. Store in a cool, well ventilated area. Check containers periodically for corrosion and leaks. Containers should be kept closed in order to minimise contamination. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. If you keep more than 2500kg or L of Dangerous Goods of Packaging Group II, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

Section 8 - Exposure Controls and Personal Protection

SWA Exposure Limits

TWA (mg/m³)

STEL (mg/m³)

sodium hydroxide

2

Peak

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday. These Exposure Standards are guides to be used in the

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd

Phone: 0432388640 (24 hours)





Product Name: Liquid Breaker Page: 4 of 8

This revision issued: April 2024

control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity. If the directions for use on the product label are followed, exposure of individuals using the product should not exceed the above standard. The standard was created for workers who are routinely, potentially exposed during product manufacture.

Biological Limit Values: As per the "National Model Regulations for the Control of Workplace Hazardous Substances (Safe Work Australia)" the ingredients in this material do not have a Biological Limit Allocated.

Engineering Measures: Ensure ventilation is adequate to maintain air concentrations below Exposure Standards. Use only in well ventilated areas. Use with local exhaust ventilation or while wearing appropriate respirator. Vapour heavier than air - prevent concentration in hollows or sumps. Do NOT enter confined spaces where vapour may have collected.

Personal Protection Equipment: RUBBER BOOTS, OVERALLS, GLOVES, APRON, SAFETY GLASSES / FACE SHIELD.







Hygiene measures: Keep away from food, drink and animal feeding stuffs. When using do not eat, drink or smoke. Wash hands prior to eating, drinking or smoking. Avoid contact with clothing. Avoid eye contact and skin contact. Avoid inhalation of vapour, mist or aerosols. Ensure that eyewash stations and safety showers are close to the workstation location.

Section 9 - Physical and Chemical Properties:

Physical Description & colour: Clear, Colourless liquid.

Odour: No odour.

Boiling Point: Approximately 100°C at 100kPa.

Freezing/Melting Point: Below 0°C.

Volatiles: Water component.

Vapour Pressure: 2.37 kPa at 20°C (water vapour pressure).

Vapour Density: No data.

Specific Gravity: Approx 1.1

Water Solubility: Completely soluble in water.

pH: 13 - 14 Volatility: No data.

Section 10 - Stability and Reactivity

Chemical stability: This material is thermally stable when stored and used as directed.

Conditions to avoid: Elevated temperatures and sources of ignition.

Incompatible materials: Oxidising agents, acids, zinc, tin, aluminium and their alloys

Hazardous decomposition products: Oxides of carbon and nitrogen, smoke and other toxic fumes.

Hazardous reactions: No known hazardous reactions...

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd Phone: 0432388640 (24 hours)





Product Name: Liquid Breaker Page: 5 of 8

This revision issued: April 2024

Section 11 - Toxicological Information

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Acute Effects

Inhalation: Material is an irritant to mucous membranes and respiratory tract.

Skin contact: Contact with skin will result in severe irritation.

Corrosive to skin - may cause skin burns. Ingestion:

Swallowing can result in nausea, vomiting, diarrhoea, abdominal pain and chemical burns to the

gastrointestinal tract.

Eye contact: A severe eye irritant. Corrosive to eyes: contact can cause corneal burns.

Contamination of eyes can result in permanent injury.

Acute toxicity

Inhalation: This material has been classified as not hazardous for acute inhalation exposure.

Acute toxicity estimate (based on ingredients): LC50 > 20.0 mg/L for vapours or

LC50 > 5.0 mg/L for dust and mist.

Skin contact: This material has been classified as not hazardous for acute dermal exposure. Acute

toxicity estimate (based on ingredients): LD50 > 2,000 mg/Kg bw

Ingestion: This material has been classified as not hazardous for acute ingestion exposure.

Acute toxicity estimate (based on ingredients): LD50 > 2,000 mg/Kg bw

Corrosion/Irritancy:

Eye: this material has been classified as a Category 1 Hazard (irreversible effects to eyes).

Skin: this material has been classified as a Category 1A Hazard (irreversible effects to

skin).

Sensitisation:

Inhalation: this material has been classified as not a respiratory sensitiser.

Skin: this material has been classified as not a skin sensitiser.

Aspiration hazard: This material has been classified as not an aspiration hazard.

Specific target organ toxicity (single exposure):

This material has been classified as a Category 3 Hazard. Exposure via inhalation may result in respiratory irritation.

Chronic Toxicity Mutagenicity:

This material has been classified as not a mutagen.

Carcinogenicity:

This material has been classified as not a carcinogen.

Reproductive toxicity (including via lactation):

This material has been classified as not a reproductive toxicant.

SAFETY DATA SHEET





Product Name: Liquid Breaker Page: 6 of 8

This revision issued: April 2024

Specific target organ toxicity (repeat exposure):

This material has been classified as not a specific hazard to target organs by repeat exposure.

Section 12 - Ecological Information

Avoid contaminating waterways.

Acute aquatic hazard: This material has been classified as not hazardous for acute aquatic exposure. Acute toxicity estimate (based on ingredients): > 100 mg/L

Long-term aquatic hazard: This material has been classified as not hazardous for chronic aquatic exposure. Non-rapidly or rapidly degradable substance for which there are adequate chronic toxicity data available OR in the absence of chronic toxicity data, Acute toxicity estimate (based on ingredients): >100 mg/L, where the substance is not rapidly degradable and/or BCF < 500 and/or log Kow < 4.

Ecotoxicity: No information available.

Persistence and degradability: No information available.

Bioaccumulative potential: No information available.

Mobility: No information available.

Section 13 - Disposal Considerations

Disposal: This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by some means. If neither of these options is suitable in-house, contact a specialist waste disposal company.

Section 14 - Transport Information

ROAD AND RAIL TRANSPORT

Classified as Dangerous Goods by the criteria of the "Australian Code for the Transport of Dangerous Goods by Road & Rail" and the "New Zealand NZS5433: Transport of Dangerous Goods on Land".

UN No: 1824

Dangerous Goods Class: 8
Packing Group: ||

Packing Group: II
Hazchem Code: 2R

Emergency Response Guide No: 37

Proper Shipping Name: SODIUM HYDROXIDE SOLUTION

Class 8 Corrosive Substances shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances where the Toxic Substances are cyanides and the Corrosives are acids), 7 (Radioactive Substances), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Poisonous Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 6 (Toxic Substances except where the Toxic Substances are cyanides and the Corrosives are acids) and 9 (Miscellaneous Dangerous Goods).

MARINE TRANSPORT

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd Phone: 0432388640 (24 hours)





Product Name: Liquid Breaker Page: 7 of 8

This revision issued: April 2024

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea.

UN No: 1824



Dangerous Goods Class: 8

Packing Group: II
Hazchem Code: 2R

Emergency Response Guide No: 37

Proper Shipping Name: SODIUM HYDROXIDE SOLUTION

Class 8 Corrosive Substances shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances where the Toxic Substances are cyanides and the Corrosives are acids), 7 (Radioactive Substances), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Poisonous Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 6 (Toxic Substances except where the Toxic Substances are cyanides and the Corrosives are acids) and 9 (Miscellaneous Dangerous Goods).

AIR TRANSPORT

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air

UN No: 1824



Dangerous Goods Class: 8

Packing Group: II
Hazchem Code: 2R

Emergency Response Guide No: 37

Proper Shipping Name: SODIUM HYDROXIDE SOLUTION

Class 8 Corrosive Substances shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), 6 (Toxic Substances where the Toxic Substances are cyanides and the Corrosives are acids), 7 (Radioactive Substances), Foodstuffs and foodstuff empties. They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.1 (Flammable Gases), 2.2 (Non-Flammable, Non-Toxic Gases), 2.3 (Poisonous Gases), 3 (Flammable liquids), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 6 (Toxic Substances except where the Toxic Substances are cyanides and the Corrosives are acids) and 9 (Miscellaneous Dangerous Goods).

Section 15 - Regulatory Information

This material is not subject to the following international agreements:

Montreal Protocol (Ozone depleting substances)

The Stockholm Convention (Persistent Organic Pollutants)

SAFETY DATA SHEET

Issued by: aiMix Chemicals Pty Ltd Phone: 0432388640 (24 hours)





Product Name: Liquid Breaker Page: 8 of 8

This revision issued: April 2024

The Rotterdam Convention (Prior Informed Consent)

Basel Convention (Hazardous Waste)

International Convention for the Prevention of Pollution from Ships (MARPOL)

This material/constituent(s) is covered by the following requirements:

The Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) established under the Therapeutic Goods Act (Commonwealth): S6. Poison.

AICIS Status: All components of this product are listed on or exempt from the Australian Inventory of Industrial Chemicals (AIIC)

Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail, 7th Edition

AICS Australian Inventory of Chemical Substances
CAS Number Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer
SWA Safe Work Australia, formerly ASCC and NOHSC

NOS Not otherwise specified

NTP National Toxicology Program (USA)

R-Phrase Risk Phrase

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

UN Number United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This SDS is prepared in accord with the SWA GH7